

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E501065  
**Report Reference** E501065-20201215  
**Date** 2021-May-13

**Issued to:** ROTEX AUTOMATION LTD  
987/11 G I D C  
MAKARPURA  
VADODARA Gujarat, 390010 IN

**This is to certify that representative samples of** SOLENOIDS FOR USE IN HAZARDOUS LOCATIONS  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** See Addendum Page

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E501065  
**Report Reference** E501065-20201215  
**Date** 2021-May-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements


USL, CNL Electric Solenoids for use in Hazardous Location, Class I, Groups B, C and D, and Class II, Groups E, F and G, Class III.

Models: Solenoid Coil II, III, or IV; followed by 24, 110, 120, 220, 240V, 50Hz/60Hz/DC, 110V 50Hz, 120V 60Hz, 230V 50Hz, 240V 60Hz, or 6, 12, 24, 48, 110, 125, 220, or 256 VDC; followed by 88; may be followed by MS, NS or NL; may be followed by CO; may be followed by SS, LC2, or FR; followed by LW0.4, LW1, LW2, LW3, LW3.5, LW5, LW8, LW13, LW15, LW20 or LW30.

Standard No. UL 1203, Standard for Explosion-Proof and Dust-Ignition-Proof Electrical Equipment for Use in Hazardous Classified Locations

Standard No. CAN/CSA C22.2 NO. 25-17 - ENCLOSURES FOR USE IN CLASS II, GROUPS E, F AND G HAZARDOUS LOCATIONS

Standard No. CAN/CSA C22.2 NO. 30-M1986 - EXPLOSION-PROOF ENCLOSURES FOR USE IN CLASS I HAZARDOUS LOCATIONS



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

