



Technická inšpekcia, a.s.

Trnavská cesta 56, 821 01 Bratislava
Slovenská republika

CERTIFICATE

no. 548/5/2021

Technická inšpekcia, a. s., Trnavská cesta 56, 821 01 Bratislava, Slovakia
notified body: 1354,

on the basis of results from assessment of full quality assurance system

notifies, that

*Rotex Automation Limited,
987/11, 12&13, GIDC-Makarpura, Vadodara-30910, Gujarat, India*

implemented and applies system of full quality assurance system (module H)

according to the European Directive 2014/68/EU on pressure equipment

Range of equipment:
Valves made of stainless steels
(see annex to the Certificate for details)

Audit Report no. 548/5/2021

Manufacturer shall inform Technická inšpekcia, a. s. of any intended change of system of full quality assurance (module H).

Certificate is valid until 9th June 2024

The Certificate validity is conditioned with performing of surveillance by Technická inšpekcia, a.s. for minimum 1 periodic audit per 12 months. Audit Report proves performing of periodic audit.

Date of Initial Notification: 4th September 2014

Bratislava, on 10th June 2021

Ing. Dušan Perniš
General Director

Annex to the Certificate no. 548/5/2021

Valve specification

Valve Design standard EN 12516-1 and ASME VIII Div. 1	Valve type	Pressure grade	Sizes
2/2 Internal pilot operated valve	21103, 21104, 21203, 21204	max. PN 40	DN40
		max. PN 70	DN50
3/2 Internal pilot operated valve	31121, 31206	max. PN 40	DN32, DN40, DN50
	31122, 31207	max. PN 70	DN32, DN40, DN50
3/2 Internal pilot operated double solenoid valve	37103	max. PN 40	DN32, DN40, DN50
	37104	max. PN 70	DN32, DN40, DN50
3/2 External pilot operated valve	32103, 32203	max. PN 40	DN32, DN40, DN50
	32104, 32204	max. PN 70	DN32, DN40, DN50
3/2 Air operated valve	33101, 33201	max. PN 40	DN32, DN40, DN50
	32104, 33202	max. PN 70	DN32, DN40, DN50
5/2 Internal pilot operated valve	51434	max. PN 40	DN32, DN40, DN50
	51435	max. PN 70	DN32, DN40, DN50
5/2 External pilot operated valve	52406	max. PN 40	DN32, DN40, DN50
	52407	max. PN 70	DN32, DN40, DN50
5/2 Air operated valve	53402	max. PN 40	DN32, DN40, DN50
	53403	max. PN 70	DN32, DN40, DN50
5/2 Internal pilot operated Double Solenoid valve	57406	max. PN 40	DN32, DN40, DN50
	57407	max. PN 70	DN32, DN40, DN50
5/3 Center Exhausted Valve	51418	max. PN 40	DN32, DN40, DN50
	51419	max. PN 70	DN32, DN40, DN50
5/3 Center Pressurised Valve	51422	max. PN 40	DN32, DN40, DN50
	51423	max. PN 70	DN32, DN40, DN50
2/2 Angle Seated Valve	65110	PN 25	DN65
	32063, 40063, 40090, 40110, 50063, 65090	PN 16	DN32, DN40, DN50, DN65
	32090, 50090, 50110	PN 24,5	DN32, DN50
	80110	PN 15	DN80

Material:

Specification	Material Grade	Valve type
ASTM A 351	CF8, CF8M	All types referred in Annex except 2/2 Angle seated valve
ASTM A 351	CF3M	2/2 Angle seated valve